

Action Clear Top Coat- Aerosol

Product Data Sheet

Product Name	Action Clear Coat Aerosol
Container	350g Aerosol Can
Base	Solvent/ Urethane
Description	A high performance, quick curing, top coat that dries hard and clear to protect metal surfaces from corrosion for multiple years.
Features	<ul style="list-style-type: none">- Suitable for all metals including; stainless steel, iron, copper, brass, aluminium, bronze, and galvanized steel.- Dries hard and non-tacky.- UV, heat and cold resistant which reduces yellowing and cracking.- Contains salt inhibitors and repels water.- Touch dry in 15 minutes- preventing impurities in the atmosphere sticking to the metal surface.- Excellent chemical resistance.- Extends the life of the metal.- No odour once dry- Top coat; Compatible with most paints.
Colour	Clear
Gloss	Gloss Finish
Dry Film Thickness	Minimum of 2 to 3 coats = Minimum 55-75 microns must be achieved.
Theoretical Coverage Rate	Each aerosol will coat approximately 5 metres squared (1 coat)
PWMIR Level	1.697 (Approx.)
Limitations	Must be touched up after 12 months and reapplied after 2 years for full-continued protection.
Surface Preparation	All surfaces must be cleaned of any dirt, grease, and previous coating. All surfaces must then be wiped down with general purpose thinners before applying the product. The surface must also be completely dry.

Action Clear Top Coat- Aerosol

Product Data Sheet

Application Process	<ul style="list-style-type: none">-Allow 30 minutes between coats to dry.-Ensure the temperature is above 10 degrees Celsius and the humidity is below 85% when applying.-Spray on an inconspicuous area first to ensure suitability of finish for desired results.-Apply a minimum of 2 coats for indoor use. Apply a minimum of 3 coats for outdoor use.-With each application, ensure the can is sprayed in an even sweeping motion at a 45 degree angle.-Once finished, turn can upside down and spray to clear nozzle.- If applying on top of paint, ensure paint has completely dried as fumes can affect the Action Clear Top Coat. <p>Extreme Metal Loss Apply 4 heavy coats to the surface with extreme metal loss, focusing on the sharp edges. The coating will prevent further damage and metal loss.</p>
Curing Schedule	<p>Touch dry in 15 minutes. Ready for the next coat in 30 minutes. Completely cured in: 7 to 14 days to full hardness.</p>
Clean up	<p>Action Clear Coat can be removed and overspray cleaned up with general purpose thinners or acetone.</p>
Safety	<p>Please see MSDS and read label warnings before using this product. Follow MSDS instructions if there is a danger to safety. Employ normal workmanlike safety precautions. Always wear personal protective equipment including a NOISH respirator that meets Australian standards, protective eyewear, gloves and overalls. Always use product in a well ventilated area. For medical advice contact the poisons information center on 13 11 26.</p>
Maintenance	<p>Touch up in 12 months, reapply in 24 months. When used externally, Action Clear Coat requires regular rinsing down with fresh water. The use of a scourer or cleaning products may damage this product.</p>
Packaging, Handling & Storage	<p>This product is under pressure. Store away from heat and out of the sun.</p>
Caution	<p>This product contains flammable solvents. Keep away from sparks and open flames.</p>
Shelf Life	<p>24 months at 23 degrees Celsius. Actual stated shelf life when kept at recommended storage conditions and in original unopened containers.</p>

Action Clear Top Coat- Aerosol

Product Data Sheet

Storage Temperature & Humidity	4-38 Degrees Celsius 0-95% Relative Humidity
Disposal	Do not puncture or incinerate can even when empty. Dispose of can in accordance with local applicable regulations.
Warranty	We assume no responsibility for coverage, performance, injuries or damages resulting from use. Action Corrosion's sole obligation, if any, is to replace or refund the purchase price of the Action Corrosion product(s) proven to be defective, at Action Corrosion's option. Action Corrosion shall not be liable for any loss or damage. No other warranty or guarantee of any kind is made by Action Corrosion, express or implied, statutory, by operation of law, or otherwise, including merchantability and fitness for a particular purpose. All trademarks referenced above are the property of Action Corrosion Pty Ltd unless otherwise indicated.
Manufacturers Details	Action Corrosion Pty Ltd 3/18 Industry Drive, Tweed Heads South, NSW 2486 Ph: 07 5524 2990 E: admin@actioncorrosion.com.au W: www.actioncorrosion.com.au