

Rustproof Clear Aerosol

Product Data Sheet

RUSTPROOF
CLEAR

Product Name	Rustproof Clear Aerosol
Container	350G Aerosol Can
Base	Solvent / Urethane
Description	A clear high performance protective coating which is quick curing and dries hard to protect metal surfaces from corrosion and plastics from deterioration from the sun.
Features	<ul style="list-style-type: none">- Superior underbody protection for 4WD's and caravans.- Excellent protection for boat trailers.- UV, heat and cold resistant which reduces yellowing and cracking.- Contains salt inhibitors, repels water and has great chemical resistance.- Touch dry in 15 minutes- preventing impurities from the atmosphere sticking to the surface.- No odour once dry- Compatible with most paints
Colour	Clear
Gloss	Gloss Finish
Dry Film Thickness	Minimum of 3 heavy coats = Minimum 75 microns on metal surfaces. Minimum of 2 coats = minimum of 55 microns on plastic surfaces.
Theoretical Coverage Rate	Each aerosol will coat approximately 5 square meters (1 coat).
PWMIR Level	1.697 (Approx.)
Limitations	Must be reapplied after 12 months for full-continued protection subject to the conditions.
Surface Preparation	All surfaces must be cleaned of any dirt, grease, and previous coating. All surfaces must then be wiped down with general purpose thinners before applying the product. The surface must also be completely dry.
Application Process	<ul style="list-style-type: none">-Allow 30 minutes between coats to dry.-Ensure the temperature is above 10 degrees Celsius and the humidity is below 85% when applying.-With each application, ensure a thick coat is sprayed in an even, sweeping motion at a 45 degree angle.-Once finished, turn can upside down and spray to clear nozzle.

Rustproof Clear Aerosol

Product Data Sheet

Application to Specific Craft	Vehicle/Trailer- Box & Boat/Caravan/Truck <ul style="list-style-type: none">- Underbody including chassis- Interior metal surfaces; inside doors and floors- Plastics- rejuvenate faded guards, side steps, handles and other fittings- Accessories- superior protection for bull bars and other attachments- All metals including welds and hardware
Curing Schedule	Touch dry in 15 minutes. Ready for the next coat in 30 minutes. Completely cured in: 7 to 14 days to full hardness.
Clean up	Rustproof Clear can be removed and overspray cleaned up with general purpose thinners or acetone.
Maintenance	When used externally Rustproof Clear requires regular rinsing down with fresh water. The use of a scourer or cleaning products may damage this product.
Safety	Please see MSDS and read label warnings before using this product. Follow MSDS instructions if there is a danger to safety. Employ normal workmanlike safety precautions. Always wear personal protective equipment including a NIOSH respirator that meets Australian standards, protective eyewear, gloves and overalls. Always use product in a well-ventilated area.
Packaging, Handling & Storage	This product is under pressure. Store away from heat and out of the sun.
Caution	This product contains flammable solvents. Keep away from sparks and open flames.
Shelf Life	24 months at 23 degrees Celsius. Actual stated shelf life when kept at recommended storage conditions and in original unopened containers.
Storage Temperature & Humidity	4-38 Degrees Celsius 0-95% Relative Humidity
Disposal	Do not puncture or incinerate can even when empty. Dispose of can in accordance with local applicable regulations.

Rustproof Clear Aerosol

Product Data Sheet



Warranty

We assume no responsibility for coverage, performance, injuries or damages resulting from use. Action Corrosion's sole obligation, if any, is to replace or refund the purchase price of the Action Corrosion product(s) proven to be defective, at Action Corrosion's option. Action Corrosion shall not be liable for any loss or damage. No other warranty or guarantee of any kind is made by Action Corrosion, express or implied, statutory, by operation of law, or otherwise, including merchantability and fitness for a particular purpose. All trademarks referenced above are the property of Action Corrosion Pty Ltd unless otherwise indicated.

Manufacturers Details

Action Corrosion Pty Ltd
3/18 Industry Drive, Tweed Heads South, NSW 2486
Ph: 07 5524 2990
E: admin@actioncorrosion.com.au
W: www.actioncorrosion.com.au